

FSI 27T

Brochure

Stump Cutter for pto 35-80 hp

FSI 27T is an attachment for tractors and similar machines with a PTO outlet.

The frame and 3-point linkage (cat. 1/2) ensure stability during grinding.

All movements are controlled via the joystick, the control box also has an option to adjust the speed of the swing movement.

Includes joystick control and PTO shaft.

Hydraulic

Tractor power requirement	27-60 kW/35-80 hp
Oil flow	Max 35 l/min
Oil pressure	Max 180 bar
Hydraulic connections	Pressure + return + leak
Hydraulic QR couplings	3 x 1/2"

PTO Speed	540 rpm
PTO with freewheel	Included

Cutting Head

Cutting disc diameter	470 mm
Tooth system	3 x turnable
Tooth diameter	20,5 mm
No of teeth's	20
Cutting disc drive	V-belt system
Sweep	Hydraulic sweep
Extend	Hydraulic 300 mm

Cutting dimensions

Cutting height above ground	400 mm
Cutting depth below ground	400 mm
Cutting sweep width	1400-1750 mm (extend)
Sweep speed	Adjustable
Hydraulic toplink	Included



FSI 27T

Brochure

Stump Cutter for pto 35-80 hp

Operator control

Joystick control Electro hydraulic

Measurements

Length 2000 mm
Width 1350 mm
Height 1200 mm
Weight 360 kg

Capacity by cutting

Average time for grinding stumps .

ø400 mm: 6 min.
ø650 mm: 12 min.
ø1050 mm: 35 min.

All based on figures from users grinding stumps 15 cm high to 15 cm below ground

