

FSI 65H 165-200

Brochure

Hydraulic Stump Cutter for 165-200 l/min.

FSI 65H is a stump grinder attachment for excavators. The recommended excavator size is 12 - 20 t.

The 65H is attached using a tool grip/coupling and the grinding movement is performed via the excavator.

Includes uncoated top plate to weld on the tool grip.



Hydraulic

Power requirement	Maks 117 kW/160 hp
Oil flow	165-200 l/min.
Oil pressure	Max 350 bar
Hydraulic connections	Pressure + return + leak
Hydraulic QR couplings	2 x 1" + 1 x 1/2" (leak)



Cutting Head

Cutting disc diameter	720 mm
Tooth system	3 x turnable
Tooth diameter	28,0 mm
No of teeth	28
Cutting disc drive	Directe
Cutting direction	90 dg. adjustable

Un painted baseplate	Standard
----------------------	----------



FSI 65H 165-200

Brochure

Hydraulic Stump Cutter for 165-200 l/min.

Measurements

Length	1100 mm
Width	720 mm
Height	905 mm
Weight	520 kg

Capacity by cutting

Average time for grinding stumps .

ø400 mm:	3 min.
ø650 mm:	6 min.
ø105 mm:	15 min.

All based on figures from users grinding stumps 15 cm high to 15 cm below ground

