

FSI 65T

Brochure

Stump Cutter for PTO 70-120 hp

FSI 65T is an attachment for tractors and similar machines with a PTO outlet.

The frame and 3-point linkage (cat. 1) ensure stability during grinding.

All movements are controlled via the joystick, the control box also has an option to adjust the speed of the swing movement.

Includes joystick control and PTO shaft.



Hydraulic

Tractor power requirement	53-90 kW/70-120 hp
Oil flow	Max 90 l/min.
Oil pressure	Max 180 bar
Hydraulic connections	Pressure + return + leak
Hydraulic QR couplings	3 x 1/2"

PTO Speed	540 rpm
PTO with freewheel	Included

Cutting Head

Cutting disc diameter	720 mm
Tooth system	3 x turnable
Tooth diameter	28,0 mm
No of teeth's	28
Cutting disc drive	V-belt system
Sweep	Hydraulic sweep
Extend	Hydraulic 600 mm

Cutting dimensions

Cutting height above ground	600 mm
Cutting depth below ground	500 mm
Cutting sweep width	1400-2200 mm (extend)
Sweep speed	Adjustable



FSI 65T

Brochure

Stump Cutter for PTO 70-120 hp

Operator control

Joystick control Electro hydraulic

Measurements

Length 3200 mm
Width 1520 mm
Height 1700 mm
Weight 700 kg

Capacity by cutting

Average time for grinding stumps .

ø400 mm: 3 min.
ø650 mm: 6 min.
ø1050 mm: 15 min.

All based on figures from users grinding stumps 15 cm high to 15 cm below ground

