

# FSI H40S-5 80-110

Brochure

## Hydraulic Stump Cutter w/sweep and 5 x hoses for 80-110 l/min.

FSI H40S-5 is a stump grinder attachment for loaders and tool carriers where the swing movement is controlled from existing outlets.

This requires the connection of 2 x pressure/return lines and 1 x pressureless return line on the tool carrier.

The H40S-5 is attached using a tool grip/coupling. The swing movement is performed using two cylinders controlled from a double-action outlet.

The machine is equipped with a flange to attach the tool grip. Includes hydraulic hoses.



### Hydraulic

Power requirement	29-48 kW/40-65 hp
Oil flow	80-110 l/min.
Oil pressure	Max 250 bar
Hydraulic connections	2 x Press/return + leak
Hydraulic QR couplings	2 x 5/8" + 2 x 1/4" + 1 x 1/2"

### Cutting Head

Cutting disc diameter	470 mm
Tooth system	3 x turnable
Tooth diameter	24,5 mm
No of teeth	16
Cutting disc drive	Direct
Sweep	Hydraulic sweep
Working area	700 mm (2 x 37 dg.)

### Operator control

From the tool carrier

Attachment base plate      Include



FSI power-tech aps  
Erhvervsparken 4B  
DK-7160 Tørring  
+45 7580 5558  
sales@fsi.dk

# FSI H40S-5 80-110

Brochure

**Hydraulic Stump Cutter w/sweep and 5 x hoses for 80-110 l/min.**

## Measurements

Length	1240 mm
Width	800 mm
Height	620 mm
Weight	260 kg

## Capacity by cutting

Average time for grinding stumps .

ø400 mm:	7 min.
ø650 mm:	18 min.
ø105 mm:	45 min

All based on figures from users grinding stumps 15 cm high to 15 cm below ground